

XFG10

1/2


VDE Code: A-DF(ZNB)2Y



Non-metallic outdoor fibre optic cable, rodent resistant

Applications and features

- Outdoor, non-metallic structure
- Rodent resistant
- High pulling force
- Suitable for duct installation by pulling or blowing
- Longitudinally water blocked with gel
- Loose tube, fully filled with thixotropic water-blocking gel



Design

1. FRP central strength element
2. Optical fibres
3. Gel-filled tube
4. Filler
5. Interstices filled with gel
6. Rip cord
7. Wrapping tape
8. Glass fibre yarns
9. PE outer sheath

Product description

This fibre optic cable contains from 5 to 12 loose tubes, stranded around a fibre-reinforced plastic (FRP) central element. If the fibres occupy fewer than 5 tubes the remaining tube positions are taken by fillers. Each tube contains up to 12 fibres in a thixotropic water-blocking gel.

A wrapping tape around the tubes separates the interstitial gel from the low-friction PE sheath and helps to maintain the circular form of the cable.

A layer of glass fibre yarns increases the rodent resistance and gives the cable excellent mechanical strength. If required the PE outer sheath can be replaced by an HLF (halogen-free, flame-retardant) sheath.



XFG10

Mechanical Specifications

XFG10						
Number of fibres (*)	up to 36	up to 60	72	96	120	144
Number of tubes	6	5	6	8	10	12
Fibre per tube (max.)	6	12	12	12	12	12
Tube diameter (mm)	2.1	2.8	2.8	2.8	2.8	2.8
Cable diameter, approx. (mm)	12	13	14	16	18	20
Outer sheath thickness (mm)	1.5					
Weight, approx. (kg per km)	115	140	165	205	255	310
Max. pulling force during (**)						
- installation (N)	5.000	6.000	7.500	8.000	8.000	8.000
- operation (N)	3.000	3.500	4.500	5.000	5.000	5.000
Crush resistance (N/10cm)	4.000					
Min. bending radius						
- with tensile load	20 x cable diameter					
- without tensile load	15 x cable diameter					
Temperature range						
- operation	- 30°C to + 60°C					
- storage	- 40°C to + 70°C					
Tested according to	IEC 60794-1					

(*) other fibre numbers by request
 (**) higher pulling force by request

Marking

"EUPEN + Product code + Fibre number/type + metric marking"

Lengths

Standard lengths: 1.000 m, 2.000 m or 4.000 m, +/- 2%
Engineered lengths: by request

